



A division of Advanced Machine & Engineering

WHITE PAPER

TOMBSTONE TESTING FOR DYNAMIC PERFORMANCE

Because tombstones support the workpiece during machining, their dynamic response becomes part of the entire system. The goal of this effort was to measure the dynamics individually and then as part of a machine setup. All tests were conducted by Dr. Tony L. Schmitz, a world renowned mechanical engineering professor at the University of Tennessee, Knoxville and joint faculty at Oak Ridge National Laboratory, who specializes in machine tool research and manufacturing engineering.

TOMBSTONE TESTING FOR DYNAMIC PERFORMANCE

Hennig Worldwide has been a global leader since 1950, specializing in chip and coolant management, machine protection, and facility safety. We work with a wide variety of manufacturers and other facilities worldwide, helping them create and maintain safe and efficient workplaces. Our commitment to excellence extends beyond our services—we actively contribute to local communities, create regional jobs, and support the global needs of machine tool customers.

TABLE OF CONTENTS

Introduction	02
Testing Set-Up and Procedure	03
Individual Testing Set-up and Procedure	03
Free Vibration Response Results	03
Frequency Response Function Results	04
<i>Cast Iron</i>	04
<i>Steel</i>	05
<i>Aluminum</i>	05
Machine Testing Set-Up and Procedure	06
Machine Testing Results	06
<i>Results for X-Direction</i>	06
<i>Results for Z-Direction</i>	06
Conclusion	06

DR. TONY L. SCHMITZ

University of Tennessee, Knoxville

Professor, Mechanical, Aerospace, and Biomedical Engineering Department


Oak Ridge National Laboratory

Joint Faculty

CHRISTINE SCHMITZ

MakingChips

Contributing Author





INTRODUCTION

Typically most tombstones in the U.S. are made from cast iron, steel, or aluminum.

Cast iron and steel are heavy, have good damping (vibration reduction) properties, and are less expensive than aluminum. Aluminum is lighter which increases slide acceleration, but it has poor damping properties and is more expensive than cast iron.

There is a weight limit on machine tool tables and pallets (where tombstones are mounted) and heavy cast iron or steel tombstones along with heavy vises and clamps can exceed the weight limit and limit the available acceleration. This is why some choose aluminum, which avoids the weight issue. However, with aluminum, there can be a vibration problem.

Excessive vibration makes tools wear faster, which is expensive; it also reduces the part quality by increasing surface roughness. Epoxy mineral tombstones offer an alternative to cast iron, steel, and aluminum materials. Made of a mixture of crushed stone and an epoxy bonding agent, they weigh less than cast iron and steel with increased vibration damping over aluminum.

TESTING SET-UP AND PROCEDURE

Because tombstones support the workpiece during machining, their dynamic response becomes part of the entire system. The goal of this effort was to measure the dynamics individually and then as part of a machine set up. All tests were conducted by Dr. Tony L. Schmitz, a world renowned mechanical engineering professor at the University of Tennessee, Knoxville and Joint Faculty at Oak Ridge National Laboratory, who specializes in machine tool research and manufacturing engineering.

INDIVIDUAL TESTING SET-UP AND PROCEDURE

Four tombstones were tested individually: cast iron (hollow), steel (hollow), aluminum (hollow), and epoxy (solid). Each was placed on a thick rubber mat during testing to eliminate boundary condition effects, such as bolt torque and mounted surface flatness. The tombstones were excited by an instrumented hammer and the response was measured using an accelerometer (not shown). See Figure 1.

Two tests were completed. First, the free vibration response due to an impulse (hammer strike) was measured. The purpose was to compare the decay rates for the tombstone vibration (or “ringing”) caused by the force input. A quicker decay means vibrations stop sooner.

Second, the frequency response function was measured. This is the ratio of the vibration response to the force in the frequency domain. It enables the natural frequency, stiffness, and damping ratio to be determined for each vibration mode. Collectively these describe how a system vibrates due to a cutting force.




Figure 1

FREE VIBRATION RESPONSE RESULTS

The maximum acceleration was normalized to one for all tests so a direct comparison was possible for the four tombstones. An exponentially decaying trend was then fit to each free vibration response (red lines), where a faster decay rate indicates higher damping. Ultimately, more damping means more stable machining. It is observed that the vibration stops much sooner for the epoxy. This means higher damping. See below.




Figure 2

Figure 3: This result demonstrates that the epoxy tombstone offers significantly higher damping than the other materials. For example, the decay rate for the epoxy is 15 times higher than aluminum for the two tombstones tested.

Material	Exponential Decay Rate	Normalized	Increase for Epoxy Over Others
	r		
Cast Iron	-15	16.7%	6x
Steel	-9	10%	10x
Aluminum	-6	6.7%	15x
Epoxy	-90	100%	-

Figure 3

FREQUENCY RESPONSE FUNCTION RESULTS

All four tombstones were tested (no top cap) to find the first bending mode and then determine the modal parameters (natural frequency, stiffness, and damping ratio) for this mode. This enables a comparison of both stiffness and damping for each material.

Figure 4: The final row gives the product of the stiffness (N/m) and damping ratio (%). A larger number is better. This result shows that the epoxy tombstone outperformed all other tombstones that were tested for the first bending mode. For example, the epoxy tombstone has a 25.2x greater dynamic stiffness (i.e., the product of stiffness and damping ratio) than the aluminum tombstone.

Modal Parameter		Cast Iron	Steel	Aluminum	Epoxy
Natural Frequency	Hz	1350.0	1651.4	1266.5	2193.9
Stiffness	N/m	7.24×10^9	6.12×10^9	1.62×10^9	10.9×10^9
Damping Ratio	%	0.23	0.16	0.20	0.75
Dynamic Stiffness	N/m	1.67×10^9	0.979×10^9	0.324×10^9	8.18×10^9
Dynamic Stiffness Ratio	-	4.89x	8.36x	25.2x	-

Figure 4

CAST IRON

Figure 5 shows the comparison of the frequency response functions for the hollow cast iron (no cap) and solid epoxy tombstones. Because the largest peak for the cast iron tombstone is larger than the largest peak for the epoxy tombstone, the epoxy tombstone offers higher dynamic stiffness. With the top cap in place, however, it is believed that the two would be comparable.




Figure 5

STEEL

Figure 6 shows the comparison of the frequency response functions for the hollow steel (no cap) and solid epoxy tombstones. Note that the steel tombstone did not have a center rib. There are subsequently many additional vibration modes due to the motion of the unsupported face between the two side edges. Because the largest peak for the steel tombstone is larger than the largest peak for the epoxy tombstone, the epoxy tombstone again provides higher dynamic stiffness overall.




Figure 6

ALUMINUM

Figure 7 shows the comparison of the frequency response functions for the hollow aluminum (with cap) and solid epoxy tombstones. A smaller peak means a stiffer mode. A broader peak means higher damping. Because the largest peak for the aluminum tombstone is much larger than the largest peak for the epoxy tombstone, it is concluded that the epoxy tombstone will outperform the aluminum tombstone in machining applications.





Figure 7

MACHINE TESTING SET UP AND PROCEDURE

Figure 8: Down (Climb) Milling



The objective of this testing was to measure tombstone motion (acceleration) during machining to compare magnitudes. In reference to Newton's second law of motion (often stated as $F=ma$), the measurement of acceleration is a measurement of the response to a force. In this set of results, more damping provides smaller acceleration.

The work material consisted of low carbon steel. Down (climb) milling cuts were performed in two locations (front and side) on each tombstone with a 2" diameter, three insert face mill. The tombstone motion was measured for each cut using an accelerometer, with 0.002" per tooth feed, 0.1" axial depth of cut, and 1336 rpm spindle speed. See figure 8.


A three insert face mill was selected. In the front set up, the workpiece was bolted onto the first (top) and third row of holes. Motion was measured in x (feed) direction. For the side set up, the workpiece was bolted onto the first (top) and fifth row of holes. Motion was measured in the z (feed) direction. Tombstones were mounted in the machine tool with workpieces bolted to the tombstone front and side faces. Tombstones were mounted on support blocks, not the machine table.

MACHINE TESTING RESULTS

The acceleration signals were measured and the root mean square (RMS) was recorded for each. The four tombstone results were then compared by computing the percent change from the cast iron results (considered the industry standard). The epoxy tombstone performed at a comparable level to the steel and cast iron tombstones, while vibration levels for the aluminum tombstone were much higher than cast iron, steel, and epoxy.


Results for X-Direction

These results show the RMS acceleration values from the steel workpiece machining tests on the front face of the tombstones: cast iron (0.77), steel (0.84), epoxy (0.86), and aluminum (1.15). The figure identifies the percent change from the cast iron baseline. Steel and epoxy vibration levels are approximately 10% higher, while aluminum is nearly 50% higher.



Results for Z-Direction

These results show the RMS acceleration values from the steel workpiece machining tests on the side face of the tombstones: cast iron (1.91), steel (1.94), epoxy (1.82), and aluminum (3.05). The figures again display the percent change from cast iron. In this case, the epoxy tombstone outperformed all others, while aluminum resulted in a 60% vibration level increase over cast iron.



Conclusion

Epoxy mineral tombstones offer a significant advancement that can improve machining processes by decreasing weight while offering sufficient dynamic stiffness. It was demonstrated that machining performance was comparable to the more traditional cast iron material choice. In practice, the epoxy material provides a flexible platform that can accommodate multiple fixture steps and operations, minimizes thermal expansion, reduces mass, and manages vibration.



A HENNIG COMPANY

DESIGN. BUILD. **GROW.**

From initial inquiry and interaction with our robust sales network and interactions with post-sale support, AME is in your corner and an extension of your team, every step of the way. Next time you're wrestling with a complex machining challenge, be sure to tag us in. We love nothing more than getting Design, Build, Grow done together.

2500 Latham Street
Rockford, IL 61103
815.962.6076

ame.com

Tombstone Testing for Dynamic Performance 0526