

|||| HENNIG®

PROTECT YOUR SUCCESS

MACHINE ROOF BELLOW COVERS

LIGHTWEIGHT, MOVABLE FOLDING COVER FOR MACHINE TOOLS

Protect against dust, particles, and other debris from escaping or entering the roof of the machine tool

TECHNICAL DETAILS

- 2 ply, rigid polyester (PET) sheets with polyurethane (TPU) coating on both sides (1 mm thick)
- Temperature resistance -20°C (-4°F) to 100°C (212°F)
- Width up to 8,000 mm
- Standard fold depth 125 mm (up to 330 mm)
- Speed up to 90 m/min
- Acceleration up to 1g
- Transverse beams made of aluminum hollow profile
- White, translucent fold material provides an optimum brightness in the working area
- Motorized version for opening and closing
- Individual folding segments are replaceable
- Decoupling option for crane loading and unloading
- Material for special applications available upon request
- Implementation can be completed with a pre-existing or new/customized slide way
- Slide way systems depending on requirements (rollers, gliders, slide ways)



ISO 9001:2015
REGISTERED

QUOTE REQUEST (ROOF BELLOWS)

Please complete this form and email to info@hennig-inc.com.

COMPANY

Company Name _____
Company Address _____

Name _____
Title _____
E-mail _____
Phone _____ Fax _____

APPLICATION / ENVIRONMENT

Quantity _____

Protection For ☐ Dust/Particle Containment ☐ Noise Attenuation ☐ Other (provide description below) _____

Mounting ☐ Existing rails (provide dimensions) _____ ☐ inch ☐ mm
☐ Hennig to supply rails

Machine Speed _____ Acceleration _____ (provide unit of measurement for each value)

Machine Width _____ ☐ inch ☐ mm Machine Length _____ ☐ inch ☐ mm

Notes _____

DIMENSIONS/TRAVEL

UOM ☐ inch ☐ mm

Extended Length _____ Retracted Length _____ Travel Length _____

